



## **CASOKU Automatic Transmission Fluid MV**

CASOKU Automatic Transmission Fluid MV is a premium automatic transmission fluid based on an advanced synthetic technology allowing very high performance needed for the demanding requirements of passenger cars automatic gearboxes.

CASOKU Automatic Transmission Fluid MV can be used in a broad range of automatic transmission standards and particularly suitable for 4 and 5 speeds automatic transmissions.

CASOKU Automatic Transmission Fluid MV provides outstanding oxidation and thermal stability resulting in lower deposit and harmful acidic by-product formation. Further, it helps to improve overall transmission durability and cleanliness.

### **Applications :**

- Suitable for automatic transmission of vehicles
- Power-steering system

### **CASOKU Automatic Transmission Fluid MV meets the requirements of the following industry and OEM specification :**

- GM DEXRON III
- FORD Mercon V
- Allison C-4

### **Benefits :**

- Proper frictional properties for smooth shifting and excellent anti-shudder performance
- Excellent oxidation resistance and thermal stability for long fluid life
- High shear stability
- Protection of abrasion resistance

### **Health, safety and environment :**

Based on current available information, our product is not expected to produce negative impact on health and safety when used in accordance with the recommendations provided in the Safety Data Sheet (SDS). Regarding relevant information of SDS, please request from the local distributor. The used product shall be recycled via legal channels, which may not be discharged into the sewage, land and river. Attention to environmental protection is required.



### Typical Properties :

Automatic Transmission Fluid	ATF MV
<b>Kinematic Viscosity</b> 40°C mm <sup>2</sup> /s	<b>30.15</b>
<b>Kinematic Viscosity</b> 100°C mm <sup>2</sup> /s	<b>7</b>
<b>Viscosity Index</b>	<b>200</b>
<b>Density @15°C kg/l</b>	<b>0.840</b>
<b>Flash Point(C.O.C.),°C</b>	<b>216</b>
<b>Pour Point ,°C</b>	<b>-51</b>

The above data indicate typical values of the product under normal production. From thereafter, the data for each batch of product may vary within the standard allowance of CASOKU lubricant quality without affecting the product performance. In case of any problems, please contact the distribution unit of CASOKU lubricant.

Please place it out of the reach of young children, and avoid storage in open areas such as exposure and rain, and please pay attention to ventilation when storing indoors.